置軌道使操作人員可準確方便地將紙堆送入飛達。 2. 真空氣泵爲德國Becker。

3. 側規可在推拉規間調節以滿足不同紙張需要。

4. 側、前規帶光電對位,可調節靈敏度。

5. 防障礙物准入設備可避免機器損壞/送紙至前規時會减速以使紙張準 確定位/日本NITTA傳送帶,速度可調節/傳送板使用德國花紋 不銹鋼使紙張順滑快速地傳送。

6. LED操作面板使送過程紙控制更爲便捷。


1. High quality feeder made in with 4 suckers for lifting paper and 4 for forwarding paper to ensure stable and fast paper feeding. Preload device, non-stop feeding, with max pile height up to 1600mm. The preload device is equipped with guilding rails that enable the operators to move the prepared pile to feeder accurately and conveniently. 2. Vacuum pump-German Becker.

3. Side lays can be adjusted between push and pull lays to meet different kinds of paper. 4. Side and front lays are with precise photocells whose sensitivity is adjustable.

5. The anti-obstacle device is adopted to prevent the machine from damage. Paper feeding will be slow down when the paper is about to reach front lays to achieve more accurate paper position. Japanese NITTA convey belt and its speed is adjustable. German made stainless steel is used for convey board to achieve smooth and quick paper transportation.

6. Operation panel with LED display is easier to control the feeding process.





1. 縱向全幅面送箔系統,可縱向橫向同時燙金, 减少用箔量并節省换箔時間。

用户友好型的金箔架可從機内拉出 方便金箔更换/最大金箔直徑: 250mm。

3. 鋁制橫軸可根據客户需要增至2軸,由獨立伺服控制。 日本安川Yaskawa伺服系統。

更加合理,及環境友好/球墨鑄鐵蜂巢版,可達到最小熱變形。

5. 縱橫雙向配有金箔分離吹氣裝置適用于大面積燙金。

6. 人機互動觸摸功能可設置不同的長拉與短拉 /如金箔長度短于6m將觸發警報 /計算機處理金箔監控系統顯示剩餘及已用金箔長度。

2. The longitudinal shaft is made of Aluminum and can be set up to 6 shafts with independent servo control depending on customer's demand. The servo system is from Japan, Yaskawa. Brush roller is applied for waste foil. Foil holder can be pulled out from machine as user-friendly

3. The transversal shaft is made of Aluminum and can be set up to 2 shafts

4. 20 individually controlled heating zone with tolerance ± 1 can distribute heat into

5. The longitudinal and transversal 2-directional air blowing foil

and long pulls. Alarm will be activated when the foil length is less than 6 m. Computerized foil monitoring system indicates used and residual foil length.

7. Optional: Foil break detector.



燙金部分 FOIL STAMPING

2. 鋁制縱軸可根據客户需要增至6軸,由獨立伺服控制 /日本安川Yaskawa伺服系統/毛刷滚輪用以清除費箔,

4.20個單獨控制加熱區,温差±1℃,可傳熱至多個小面積區域,

7. 選配: 斷箔探測器

8. 選配: 6滚筒金箔回卷裝置 型號: WFR-280. 9. 伺服馬達自動控制壓力。

1. The longitudinal full format foil feeding system make it possible to stamp the foils in longitudinal and transversal direction at the same time which helps greatly in saving waste foils as well as the time to change foil.

design to change new foil. Max. foil diameter: 250mm.

with independent servo control depending on customer's demand. The servo system is from Japan, Yaskawa.

multiple small area that is more reasonable and eco-friendly. The honeycomb board is made of ductile iron with less thermal deformation.

separation device is used for big area stamping.

6. Man-machine interface with touch function can be used to set up different short

8. Optional: 6 rollers foil rewinding unit Model: WFR-280.

中國・國望集團 國望科技(浙江)有限公司 CHINA · GUOWANG GROUP **GUOWANG TECHNOLOGY (ZHEJIANG) CO., LTD**

浙江省平阳县万全轻工机械园区 Wanquan Light Industry Machinery Park, Pingyang Country, Zhejiang Province T+86-577-58111111 F+86-577-58111077 E master@guowang.com

WWW.GUOWANG.COM

SHANGHAI EUREKA MACHINERY IMP.& EXP.CO..LTD

Room 17011727 Fourune Times Manison No.1438 Shanxi Rd(n) Shanghai P.r.china T+86-21-62998061 62986517 62999507 F+86-21-62985160 E Info@eureka-machinery.com

WWW.EUREKA-MACHINERY.COM



中國・國望集團

GUOWANG

HOT STAMPING MACHINE

自动烫金&模切-E 系列

KEEP IMPROVING TO WIN MORE **EXPECTATION**

不斷超越,才能贏得更多期待

PURSUING GERMAN AND JAPANESE QUALITY TO SHAPE A NATIONAL BRAND. 追求德日品質 塑造民族品牌

服務爲一體的中國印後設備專業制造商。經30多年發展積累,現有占地 equipment in China that integrates research and development, design, production, sales, and sovices. After more than 20 years of death and development, design, production, sales, and sovices. 面積近12萬平方,建築面積超20萬平方的現代化標準工廠。并在全球 factory with an area of nearly 120,000 square meters and a construction area of over 設有銷售、售後服務網點。準時爲客户提供優質快捷的售前售後服務。

不斷超越,才能贏得更多期待。公司按照國際企業的標準及架構,執行 Only by constantly surpassing to win more expectations. The company implements the 7S現場管理模式。公司引進50多臺國際大型加工中心,有日本三菱、 的執着追求,强大的加工集群是您設備品質的堅定保證。

國望集團通過ISO9001質量管理體系認證,主要產品均已通過歐盟CE 以及德國TUV認證,匯集全球優勢資源,融合國際前沿技術,精益求精 The Guowang Group has obtained is obtained is obtained is obtained is obtained in Supplier of the EUCE and German TUV certification. The company 求,重新定義印後裝備價值,賦予用户强大的市場競争力,爲客户創造

中國·國望集團始創于1993年,是一家集研發、設計、生産、銷售、 The Guowang Group, founded in 1993, is a professional manufacturer of post-press and services. After more than 30 years of development, it now has a modern standard 200,000 square meters. And has sales and after-sales service outlets worldwide. providing customers with high-quality and efficient pre-sales and after-sales services on time.

7S on-site management mode according to the standards and framework of top international companies. It has introduced more than 50 international advanced 東芝、馬扎克、大隈、瑞士斯達拉格、意大利帕瑪、曼德利等高精度加 large-scale machining centers, including high-precision machining equipment such as 工設備,同時引進瑞士海克斯康三坐標檢測儀,祇因對産品精度和品質 Mitsubishi, Toshiba, Mazak, Okuma, Staubli, PAMA, and Mandelli from Japan, Switzerland, and Italy. At the same time, the company has introduced the Swiss Hexagon three-coordinate measuring instrument. With its persistent pursuit of product precision and quality, the strong machining cluster is a firm guarantee for your equipment quality.

The Guowang Group has obtained ISO9001 quality management system certification, 全力打造新一代印後設備,以智能化、高精度、高效率、高品質的要 gathers global advantageous resources, integrates international cutting-edge technology, and strives to create a new generation of post-press equipment with intelligent. nigh-precision, high-efficiency, and high-guality requirements. It redefines the value of post-press equipment and gives users strong market competitiveness, creating maximum benefits for customers









國望產品包括:全自動燙金機、模切機、卷筒分切機 切紙機、取紙機、卸紙機、升降機、闖紙機等高品質印後設備。

Guowang's products include high-quality post-printing equipment such as fully Automatic hot stamping machines, Die-cutting machines, Roll slitters, Paper cutters, Paper loader, Paper unloader, Lifting machine, and Jogger.

E 105 Y

Automatic hot stamping machine

自動燙金、模切機

燙金實則是印刷藝術中對美的追求。它是關注極致細節的質量突出。當您期望獲得高質 量的燙金質量與效果時,我們的燙金設備是您當之無愧的選擇。它最多可裝配六縱、 六息(防僞)、二横,可供您根據産品的需求進行任意選擇。操控系統配有19、15、 10.4寸LED三屏兼容觸摸屏控制系統,在觸摸屏導航設置功能中可對紙張印刷圖案 的 套準進行任意精確調整。在匀步式和跳步式的燙印過程中,電化鋁箔的間距可最小調至 1mm,從而使您有效的節約成本和提高效率。機械部位經過德國專業博士和日本工程師 的重新設計,使燙印運轉過程中可達到350噸的壓力,使得燙印、凹凸呈現出更加立體


Foil-stamping is actually the pursuit of beauty in the graphic arts and it focus more on the quality in details. Our machine would be your good choice if you prefer high foil-stamping quality. Can be installed with at most 6 foil feeding units in longitudinalway, 2 in transversal way and 6 for hologram for your otpions for different jobs. 19 inch LED touch screen from with you can adjust the regis tration of the printed image on the sheets precisely. The distance between the foils can be adjusted to Min.1mm in the way of step ping or skipping foil-stamping that help you to save cost and be efficient. The mechanical units are re-designed by the specialists from Germany and Japan that enable the working pressue to reach 350 tons for a better quality of foil-stamping and embossing with higher speed as


E 105 / E 105 Q

Automatic die-cutting machine with stripping 清廢自動模切機


模切、壓痕和冷壓或熱壓凹凸等,特别是各種高級精 細的印刷品、如烟盒、酒盒、禮品盒、小家電盒、化 妝品盒等,均可以在本機上進行模切凹凸壓痕,以獲 得富于立體感,精致美觀的印刷制品。


該機主要用于印刷包裝工業中的紙盒、紙箱、商標的 Our machine is used for paper box, paper carton, and label die-cutting, foil stamping and embossing especially on all kinds of exquisite printing materials such as the wine box, cigarette box, gift box, and household appliance box, cosmetics box to achieve 3D and exquisite














參數	SPECIFICATIONS				
	Model		E 105	E 105 Q	E105Y
用紙幅面	Max. sheet size	mm	1050x760	1050x760	1050x760
用紙幅面	Min. sheet size	mm	450x370	450x370	450x370
裁切幅面	Max. die-cutting size	mm	1045x745	1045x745	1045x745
燙金幅面	Max. stamping size	mm	/	/	1040x740
版框内尺寸	Die size	mm	1100x770	1100x770	1020x740
鋼板	Cutting plate	mm	3+1	3+1	3+1
的高度(模切刀)	Height of die-cutting rule	mm	23.8	23.8	23.8
第一把刀綫	First cutting rule	mm	13 采用附加墊時爲13	13 采用附加整時爲13	13 采用附加墊時爲
咬口大小	Gripper margin	mm	9-17	9-17	9-17
紙規格	Carton board	g/m²	90-2000	90-2000	90-2000
規格	Carton board	mm	0.1-3	0.1-3	0.1-3
紙規格	Corrugated board	mm	≤4	≤4	≤4
工作壓力	Max. cutting force I	t	300	300	320
模切速度	Max. die-cutting speed	S/H	7500	7500	7500
燙金速度	Max. stamping speed	S/H	/	/	6500
全息及鐳射燙印速度	Max. hologram speed	S/H	/	/	5500
堆高度(含托盤)	Feeder pile height (incl. pallet)	mm	1600	1600	1600
堆高度(含托盤)	Delivery pile height (incl. pallet)	mm	1350	1350	1350
	Zones individually controlled		/	/	20温區
温度	Temperature	C	/	/	20-200
金箔直經	Max. Foil reel diameter	mm	/	/	φ 250
紙芯直經	Foil core	inch/mm	/	/	25.4/76.2
幾功率	Main motor power	kw	11	11	11
	Total power	kw	17	17	17
	Voltage	V	380±5%	380±5%	380±5% 50HZ
组細	Cable	mm²	10	10	16
空氣	Compressed air	bar	6-8	6-8	6-8
里	Air flow	L/Min	200	200	600

安裝數據	INSTALLATION DATA				
型號	Model		E 105	E 105 Q	E105Y
A 機器外形總長度	Overall machine length	mm	5160	6150	6264
B 機器外形總寬度	Overall machine width	mm	4250	4250	4350
C 機器外形總高度	Overall height of machine	mm	2430	2430	2580
D 送紙機組長度	Feeder length	mm	2580	2580	2425
三 模切機組長度	Die-cutting length	mm	1330	1330	1500
燙金/清廢機組長度	Foil / stripping length	mm		990	1067
G 收紙機組長度	Delivery unit length	mm	1250	1250	1270
Ⅰ 機組寬度	Machine width	mm	2250	2250	2350
脚踏板寬度	Cat walk way width	mm	2000	2000	2000
」 送紙過道空間	Aisle for paper feeding	mm	3000	3000	3000
く 機器後過道寬	Aisle of machine side	mm	1500	1500	1500
出紙過道空間	Aisle for paper delivery	mm	2500	2500	2500
净重	Net weight	t	17	18.5	20.5
包裝尺寸長	Packing size length	mm	5110	6500	6500
包裝尺寸寬	Packing size width	mm	2300	2300	2300
包裝尺寸高	Packing size height	mm	2530	2530	2530

注:由于産品在不斷的改進,數據如有改動,恕不另行通知。